

Technical sheet :

MI 25 G ST5



| Technical characteristics | | | Metric |
|---------------------------|---|------------------|----------------------------|
| 1.1 | Manufacturer | | MANITOU |
| 1.2 | Model Name | | MI 25 G ST5 |
| 1.3 | Power source | | Lpg |
| 1.4 | Operator type | | Seated |
| 1.5 | Max. capacity | Q | 2500 kg |
| 1.6 | Load centre of gravity | c | 500 mm |
| 1.8 | Load distance, centre of drive axle to fork | x | 465 mm |
| 1.9 | Wheelbase | y | 1600 mm |
| Weight | | | |
| 2.1 | Service weight | | 3895 kg |
| 2.2 | Weight on front axle (laden) / rear axle (laden) | | 5665 kg / 730 kg |
| 2.3 | Weight on front axle (Unladen) / rear axle (Unladen) | | 1665 kg / 2230 kg |
| Wheels | | | |
| 3.1 | Tyres type | | Super Elastic |
| 3.2 | Dimensions of front wheels | | 7.00-12 12 |
| 3.3 | Dimensions of rear wheels | | 6.00-9 10 |
| 3.5 | Number of front wheels / rear wheels | | 2 / 2 |
| 3.5.2 | Number of drive wheels | | 2 |
| 3.6 | Front wheel gauge | b10 | 965 mm |
| 3.7 | Rear wheel gauge | b11 | 973 mm |
| Dimensions | | | |
| 4.1 | Tilt of Mast Forward (deg) / Backward (deg) | α / β | 6 / 12 |
| 4.12 | Height of towing bar (coupling height) | h10 | 360 mm |
| 4.19 | Overall length | l1 | 4345 mm |
| 4.20 | Length to face of forks | l2 | 2115 mm |
| 4.21 | Overall width - Single wheels | b1 | 1155 mm |
| 4.21 | Overall width - Twinned wheels | b1 | 1595 m |
| 4.22 | Forks section / width / length | s / e / l | 40 mm x 122 mm / 1150 mm |
| 4.23 | Fork carriage ISO 2328 (class/form) A/B | | FEM 2A |
| 4.24 | Fork carriage width | b3 | 1038 mm |
| 4.31 | Ground clearance below mast | m1 | 115 mm |
| 4.32 | Ground clearance at centre of wheelbase | m2 | 175 mm |
| 4.33 | Aisle Width for pallets 1000 x 1200 crossways | Ast | 3930 mm |
| 4.34 | Aisle width for 800 x 1200 pallet lengthways | Ast | 4130 mm |
| 4.35 | Turning radius | Wa | 2265 mm |
| 4.36 | Internal turning radius (over tyres) | b13 | 145 mm |
| 4.7 | Height of overhead guard (cabin) | h6 | 2115 m |
| 4.8 | Seat height/stand height | h7 | 1190 mm |
| Performances | | | |
| 5.1 | Travel speed (laden / unladen) | | 19.40 km/h / 19.70 km/h |
| 5.2 | Lifting speed (laden / unladen) | | 0.55 m/s / 0.64 m/s |
| 5.3 | Lowering speed (laden / unladen) | | 0.50 m/s / 0.50 m/s |
| 5.5 | Drawbar pull (Laden / Unladen) | | 1940 daN / 1040 daN |
| 5.7 | Gradeability (laden / unladen) | | 20 % / 20 % |
| 5.10 | Service brake | | Hydraulic |
| Engine | | | |
| 7.1 | Engine brand / model | | GCT (ex-Nissan) / GK25 LPG |
| 7.2 | Engine power according to ISO 1585 | | 43.40 kW |
| 7.3 | Rated speed | | 2700 rpm |
| 7.4 | Number of cylinders / Capacity of cylinders | | 4 - 2488 cm ³ |
| Miscellaneous | | | |
| 8.2 | Working hydraulic pressure for attachments | | 160 Bar |
| 8.3 | Oil flow rate for attachments | | 75 l/min |
| 8.4 | Measured/guaranteed mean noise level at the ear of the operator | | < 80 dB |



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes